

[My PhilGEPS](#) | 
 [My Organization](#) | 
 [My Profile](#) | 
 [Opportunities](#) | 
 [Catalogue](#) | 
 [Directory](#) | 
 [About PhilGEPS](#)

[Pending Task](#) | 
 [Notices](#) | 
 [Award Notices](#)

Tuesday, June 11, 2024 08:11 AM Venus Solano MNWD [Log-out](#)

## Bid Notice Abstract

[Detail Tracking Report](#)

### Request for Quotation (RFQ)

**Reference Number:** 10942511  
**Procuring Entity:** METROPOLITAN NAGA WATER DISTRICT  
**Title:** Supply and Delivery of IT Parts and Accessories and Perip (PR#24-05-0266)  
**Area of Delivery:** Camarines Sur

[Printable Version](#)

<b>Solicitation Number:</b>	PR 24-05-0266	<b>Status</b>	Active
<b>Trade Agreement:</b>	Implementing Rules and Regulations	<b>Associated Components</b>	<a href="#">1</a>
<b>Procurement Mode:</b>	Shopping - Ordinary/Regular Office Supplies & Equipment (Sec. 52.1.b)	<b>Bid Supplements</b>	<a href="#">0</a>
<b>Classification:</b>	Goods	<b>Document Request List</b>	<a href="#">0</a>
<b>Category:</b>	Information Technology Parts & Accessories & Perip	<b>Date Published</b>	11/06/2024
<b>Approved Budget for the Contract:</b>	PHP 669,220.00	<b>Last Updated / Time</b>	11/06/2024 12:00 AM
<b>Delivery Period:</b>	60 Day/s	<b>Closing Date / Time</b>	14/06/2024 1:00 PM
<b>Client Agency:</b>			
<b>Contact Person:</b>	Venus C. Solano Procurement Analyst A 40 J.Miranda Ave., Naga City Camarines Sur Philippines 4400 63-54-4737813 Ext.117 63-54-4739288 mnwdbac@yahoo.com		

**Description**

- GENUINE PARTS FOR LENOVO THINKSYSTEM ST550 - 7X10 Serial No. J3010F3N  
SR 480GB/PM89312.5/SATA SSD  
- with 2.5" SAS Drive Tray Caddy  
- Part Number: 00YK193
- 8 sets  
ST550 Rear Fan Module Part Number: 01PE043 1 pc  
FAN, ST551 Mid Fan Module Part Number: 01PE042 2 pcs
- Full 10GE Layer 3 Core/Aggregation Switch (Ruijie - RG-CS86-20XS4VS2QXS-D)  
- 20 x 10GE SFP+ ports  
- 4 x 25GE SFP28 ports  
- 2 x 40GE QSFP+ ports  
- 760 Gbps switching capacity  
- with two AC Power Module included 1 unit
- Indoor Access Points (Ruijie - RG-AP820-L(V3))  
- max number of active devices per AP - 64  
- Max number of associated clients - 256  
- Max. number of BSSIDs - 32 (up to 16 BSSIDs per radio)  
- two power supply modes (DC and PoE++ powered)  
- with DC power adapter included 10 units
- Point to Point Bridge (Ubiquiti UBB-XG) with two 10Gb/s SFP+ AOC - 20m (66ft)  
- Networking interface: (1) GbE RJ45 port  
(1) 1/10G SFP+ port  
- Maximum Range: 500m  
- Radios: 60 GHz with 5 GHz backup