

[My PhilGEPS](#) | 
 [My Organization](#) | 
 [My Profile](#) | 
 [Opportunities](#) | 
 [Catalogue](#) | 
 [Directory](#) | 
 [About PhilGEPS](#)

[Pending Task](#) | 
 [Notices](#) | 
 [Award Notices](#)

Friday, August 4, 2023 08:06 AM Venus Solano MNWD [» Log-out](#)

## Bid Notice Abstract

[Detail Tracking Report](#)

### Request for Quotation (RFQ)

**Reference Number** 10007167  
**Procuring Entity** METROPOLITAN NAGA WATER DISTRICT  
**Title** Supply and Delivery of Ultrasonic flow Meter (PR#23-07-0324)  
**Area of Delivery** Camarines Sur

[Printable Version](#)

<b>Solicitation Number:</b>	PR 23-07-0324	<b>Status</b>	Active
<b>Trade Agreement:</b>	Implementing Rules and Regulations	<b>Associated Components</b>	1
<b>Procurement Mode:</b>	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	<b>Bid Supplements</b>	0
<b>Classification:</b>	Goods	<b>Document Request List</b>	0
<b>Category:</b>	Water Service Connection Materials/Fittings	<b>Date Published</b>	04/08/2023
<b>Approved Budget for the Contract:</b>	PHP 320,000.00	<b>Last Updated / Time</b>	04/08/2023 12:00 AM
<b>Delivery Period:</b>	30 Day/s	<b>Closing Date / Time</b>	07/08/2023 5:00 PM
<b>Client Agency:</b>			
<b>Contact Person:</b>	Venus C. Solano Procurement Analyst A 40 J.Miranda Ave., Naga City Camarines Sur Philippines 4400 63-54-4737813 Ext.117 63-54-4739288 mnwdbac@yahoo.com		

#### Description

1 Ultrasonic Flow Meter  
 Sizes: up to DN25-DN1200  
 Features:  
 - The design is compact, lightweight and easy to carry.  
 - Calculate positive and negative flow and cumulative measurement.  
 - Add SD card data automatic storage function, data will never be lost again.  
 - Advanced modular integrated design independent menu operation, large screen LCD. Backlight 4 lines display.  
 - Particularly suitable on-site flow detection for various pressure requirements.  
 - Sensor Protection: IP68  
 - Transmitter protection level: IP54  
 - PS 116 Series  
 APPLICATION:  
 - Ultra pure liquids  
 - Potable Water  
 - Raw sewage  
 - Reclaimed water  
 - Cooling Water  
 - River water  
 - Plant effluent  
 TECHNICAL DATA:  
 - Flow Range: ±0.03ft./s-±20ft/s(±0.01m/s:12m/s optional)  
 - Accuracy: ±1% of measured value  
 - Pipe Size: Clamp-on: (25mm - 1200mm)  
 - Pipe Material: Carbon Steel, stainless steel, PVC  
 - Output: Analog output: 4-20 mA, max load 7500  
 - SD Card : Storage : 1 GB  
 Max: 512 files  
 Interval: 5-60 seconds  
 - Power Supply: 11.1V rechargeable lithium battery power  
 - Keypad: Tactile Keys  
 - Keypad: Tactile Keys  
 - Display: 3.5 inch" black and whitescreen (320x240) backlit LCD  
 - Temperature: Transmitter: -10°C. . . +50°C  
 Transducer : 0°C . . . +80°C  
 Humidity: up to 99% RH, non-condensing  
 Protection: NEMA 13, IP54  
 Weight: Transmitter: approximately 1.0kg one set weight is 10kg after package  
 - Authorized distributor certificate